



GEKO

3001 E-AA/HHBA

Order Number 986211

Range of application: average electric tools hammer drills angular grinders lawn mowers light supply etc.
Compact design. Operating time with one tank fillign up to 9 hours. Automatic low oil level shut down. Starting current turn-off gain. 2x Schuko sockets.



| Attribute | Unit | Value |
|---|---------------------|--------------------------|
| Genset type | | Asynchronous |
| Electrical capacity (1~) cos ϕ 1,0 | VA | 3000 |
| Voltage (1~) | V | 230 |
| Maximum sum. current (1~) | A | 13 |
| Current (Schuko 1~) | A | 13 |
| Starting current | A 1~ | 17 |
| Frequency | Hz | 50 |
| Protection | | IP 54 |
| Engine type | | Honda GX 200 (Low Noise) |
| Cylinders | | 1 |
| Speed | U min ⁻¹ | 3000 |
| Fuel type | | Petrol |
| Engine oil capacity | l | 0.6 |
| Engine power | kW | 3.8 |
| Cooling | engine / generator | air / air |
| Fuel capcity | l | 8 |
| Operation time at full load | h | 5 |
| Operation time half load | h | 9 |
| Weight | kg | 48 |
| Dimensions | mm | 520 x 410 x 390 |
| Acoustic power | dB(A) | 96 |
| Acoustic pressure | dB(A) | 68 |
| Case | | |

| Related equipment | Order Number | Related equipment | Order Number |
|---|--------------|---|--------------|
| Exhaust hose, 904872 | 904872 | Adapter für Abgasschaluch 904878 | 904878 |
| Filler cap with lockable ventilation 900601 | 900601 | Isolation control device, without cut-off, 988641 | 988641 |
| FI-protection switch incl. earthing set, 1 ph., ... | 904370 | Wasserdichte Steckdosen 903051 | 903051 |
| GW 308 988521 | 988521 | Chassis, 988548 | 988548 |
| Lifting set, 911643 | 911643 | Voltmeter 908300 | 908300 |
| Amperemeter, 908350 | 908350 | Erdungsgarnitur 908250 | 908250 |
| Optional Economic | 988900 | | |

GEKO

EISEMANN

Metallwarenfabrik Gemmingen GmbH
Industriestrasse 1 D-75050 Gemmingen

Telefon +49 (0) 7267 806-0
www.metallwarenfabrik.com

Fax +49 (0) 7267 806-100
info@metallwarenfabrik.com